# LEGRIS
# NYLON/NICKEL-PLATED BRASS PUSH-IN MALE ELBOW




** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 02:09 AM

SKU
: 3699

MARCA
: DIXON VALVE

MODELO
: 31095620

Use:
Compatible tubing: semi-rigid nylon, polyurethane and polyethylene tube
Vacuum capability: vacuum of 28" Hg (99% vacuum)

Features:
Positive seal: sealing and holding is accomplished instantaneously
Reusable: connect and disconnect numerous times
Full flow: fitting seals on outside diameter of tubing
Pre-applied thread sealant on all tapered male pipe threads
The body is orientable for positioning purposes.
Supplied with gasket

Construction:
Nickel-plated brass threads
Black body is glass-filled nylon

Installation
Quick connect and disconnect, no tools required.
To connect, simply push tubing in.
To disconnect, press the release ring towards the fitting and pull tubing out.

Safety notes:
Maximum circuit pressure depends equally on the type and diameter of the tube used.
Pressure rating given at ambient temperature 70°F/21°C.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Factory Part Number** | 31095620 |
| **Male Thread** | Straight |
| **Male Thread Size** | 10-32 |
| **Material** | Nylon/Nickel-Plated Brass |
| **Seal** | Buna-N D seal |
| **Temperature Range** | -4°F to 175°F (-20°C to 79°C) |
| **Tube OD** | 1/4" |
| **Weight Lb** | 0.0135 |
| **Working Pressure** | 290 PSI at ambient temperature |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us