METRIC PUSH-IN MALE ELBOW BSPP



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 09:35 PM

SKU
: 3821

MARCA
: DIXON VALVE

MODELO
: 31990810

Use:
Compatible tubing: semi-rigid nylon, polyurethane and polyethylene tube
Vacuum capability: vacuum of 28" Hg (99% vacuum)

Features:
Positive seal: sealing and holding is accomplished instantaneously
Reusable: connect and disconnect numerous times
Full flow: fitting seals on outside diameter of tubing
The body is orientable for positioning purposes.

Construction:
Black glass-filled nylon body
Polypropylene release button
Nickel-plated brass threads
Silicone free

Installation
Quick connect and disconnect, no tools required
To connect, simply push tubing in.
To disconnect, press the release ring towards the fitting and pull tubing out.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	31990810
Male Thread	BSPP
Male Thread Size	1/8"
Material	Nylon/Nickel Plated Brass
Pressure Rating	290 PSI at 70°F (21°C)
Seal	Buna-N D-seal
Temperature Range	-4°F to 175°F (-20°C to 79°C)
Tube OD	8 mm
Weight Lb	0.0310

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us