STEEL 3500 MALE NIPPLE

FECHA
: 11/24/2026 12:24 AM

SKU
: 22378

MARCA
: DIXON VALVE

MODELO
: 3501



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

Use:
The constant vibration created by air tools, like air drills and pavement breakers, is destructive to air hose couplings, especially the quick-acting type. To provide protection against coupling breakage and related hazards, Dixon recommends the use of a whip hose.
To construct a whip hose, connect one end of a short (3' to 10') air hose to the air tool using a 3500 type steel nipple. Connect the other end of the hose to the air supply using the standard quick-acting coupling. The heat treated 3500 nipple will withstand vibration far better than the standard coupling and provide a safer connection. The whip hose should remain permanently connected to the tool.

Safety notes:
For air and water service only
To provide protection against coupling breakage and related hazards, Dixon® recommends the use of a whip hose.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	3501
Hose Size	1/4"
Male Thread	NPT
Male Thread Size	1/8"
Material	Zinc Plated Steel
Pressure Rating	600 PSI at 70°F (21°C)
Weight Lb	0.0600

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us