# LEGRIS STAINLESS STEEL PUSH-IN MALE ELBOW



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 01:03 AM

SKU
: 4005

MARCA
: DIXON VALVE

MODELO
: 38896218

Applications:
Suitable for many industries such as: chemical, food, packaging and medical

Use:
Compatible with a range of tubes including: semi-rigid nylon tube, flexible polyurethane tube, low density polyethylene, PTFE tube FEP 140, stainless steel and copper tube (when grooved)

Specifications:
Materials conforming to FDA and 1934/2004 CE standards

Features:
The body is orientable for positioning purposes.

Construction:
AISI 316 stainless steel body with 316L stainless steel backup washer and 303L stainless steel collet
Silicone free
FKM O-ring

Note:
Thread sealant does not come pre-applied on male threads, allowing the appropriate sealant for the application to be applied by the user.

Safety notes:
Maximum circuit pressure depends equally on the type and diameter of the tube used.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Factory Part Number** | 38896218 |
| **Male Thread** | NPT |
| **Male Thread Size** | 3/8" |
| **Material** | Stainless Steel |
| **Maximum Operating Pressure** | 290 PSI |
| **Seal** | FKM O-ring |
| **Temperature Range** | -4°F to 245°F (-20°C to 118°C) |
| **Tube OD** | 1/2" |
| **Vacuum Capability** | 28" HG |
| **Weight Lb** | 0.1700 |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us