DQC CM-SERIES INDUSTRIAL MOLD INTERCHANGE VALVED COUPLER 90° HOSE BARB





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 12:18 AM

SKU
: 4039

MARCA
: DIXON VALVE

MODELO
: 3CM9S4-B

Specifications:
Rated pressure for connected Brass Valved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 6,700 PSI (450 bar) Burst
Rated pressure for connected Brass Valved Coupler and Steel Plug: 500 PSI (35 bar) Maximum Working and 6,100 PSI (400 bar) Burst

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Silicone gaskets and valve O-rings are standard

Compatibility & Interchange Data:
Mold Coolant Interchange
Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:
Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	3/8"
Factory Part Number	3CM9S4-B
Hose ID	1/2"
Length	2.85"
Material	Brass
Maximum OD	0.95"
Temperature Range	-90°F to +400°F (-68°C to +205°C)
Weight Lb	0.3500

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us