# SANITARY PRESSURE GAUGE




** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 01:53 AM

SKU
: 4131

MARCA
: DIXON VALVE

MODELO
: 3S-F-15U-GFBTSS

Specifications:
Weight: approximately 3 lbs.
Accuracy: ± 1.5% of full scale
Over range capacity: 30%
3-1/2" dial

Features:
Rezero feature: standard on pointer

Construction:
Wetted surfaces: 316L stainless steel
Surface finishes (wetted parts): Ra max = 25 micro inches
Lens material: polycarbonate
Standard fill: food grade glycerin
Case material: 304 stainless steel

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Case** | Glycerin Filled |
| **Fitting Type** | Clamp |
| **Material** | 316L Stainless Steel |
| **Mount** | Bottom |
| **Factory Part Number** | 3S-F-15U-GFBTSS |
| **Pressure Range** | 0-200 PSI |
| **Size** | 1-1/2" |



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Temperature Range** | 0°F to 250°F |
| **Weight Lb** | 3.0000 |



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us