AG-SERIES AGRICULTURAL PUSH-PULL POPPET VALVE FEMALE THREADED COUPLER





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:08 PM

SKU
: 4859

MARCA
: DIXON VALVE

MODELO
: 4AGOF4-PV-PS

Applications:
Used on construction equipment, farm implements and most other mobile equipment

Specifications:
The International Standard Organization (ISO) has adopted specifications regarding dimensions and interchangeability.

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Steel coupler sleeves are hardened to resist deformation and maximize service life.
Nitrile (Buna-N) seals are standard
Couplers have a PTFE Anti-Extrusion ring
Poppet valve seals are crimped in place to maintain integrity during excessive flow conditions and pressurized connection.
Ball valve and poppet valve options available

Compatibility & Interchange Data:
Pioneer Agricultural Interchange
Parker/Pioneer 4000 Series
Safeway S20

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1/2"
Burst Pressure	16500 PSI (1100 Bar)
Factory Part Number	4AGOF4-PV-PS
Hex	1-1/16"
Length	2.62" (66.55mm)
Material	Steel
Maximum OD	1.49" (37.8mm)
Maximum Operating Pressure	4000 PSI (275 Bar)
Seal	Buna-N
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female ORB
Thread Size	3/4"-16
Weight Lb	0.6750

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us