HEAVY DUTY BUTTERFLY VALVE

FECHA
: 11/23/2026 11:36 PM

SKU
: 27150

MARCA
: DIXON VALVE

MODELO
: 4BF416DITF-FKM



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

Applications:
Low pressure transfer of water, acids, chemicals, slurries and other liquids
Designed for all low pressure hydraulic fracturing applications
Specifications:
Typical gauge pressures in transfer applications range from 50 to 200 PSI working pressure (MSS SP-67 spec)
Features:
Locators around the outer edge of the body allow the valve to easily line up at center
Thicker stems compared to other brands delivers a more durable and reliable performance
Grease zerk added to body neck for reliable performance
10-position throttling handle for control accuracy
For use between two lightweight, 125 lb., or 150 lb. valve flanges
Construction:
Disc: Nickle plated ductile iron with Buna-N seat (0°F to 200°F), or FKM seat (0°F to 200°F)
Bushings: PTFE
O-rings: Buna N
Stems: 416 stainless steel
Retainer pins: 304 stainless steel
Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Description	Valve with FKM seat
Material	Body: ductile iron
Factory Part Number	4BF416DITF-FKM
Size	4"
Weight Lb	13.6000
Working Pressure	200 PSI

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us