DQC HS-SERIES ISO-B STEAM INTERCHANGE FEMALE COUPLER





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:18 PM

SKU
: 22605

MARCA
: DIXON VALVE

MODELO
: 4HSBF4-B

Applications:
Designed exclusively for steam applications

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Coupler has a large plated steel sleeve designed for easy gripping with gloves
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
EPDM steam-grade seals are standard
Couplers have a redundant O-ring sealing system (Dual O-rings with PTFE back-up)
Valve seals are crimped in place to maintain integrity during excessive flow conditions.
Special high-temp EPDM O-rings designed for steam service

Compatibility & Interchange Data:
Interchangeable to ISO7241 Series 'B'
Parker 60-Series Steam Couplings

Safety notes:
Maximum working pressure has been calculated using standard saturated steam at 194°C (382°F) for general purpose continuous service. For advanced operating pressure or super-heated steam applications, contact Dixon for further information.
Warning: Do not disconnect under pressure!
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1/2"
Factory Part Number	4HSBF4-B
Hex	1-1/16"
Length	2.86"
Material	Brass
Maximum OD	2.25" (57.2mm)
Pressure Rating	Rated to 200 PSI gauge saturated steam 382°F (194°C)
Temperature Range	-70°F to +400°F (-57°C to +204°C)
Thread	Female BSPP
Thread Size	1/2"-14
Weight Lb	0.9600

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us