DUAL-LOCK P-SERIES THOR INTERCHANGE MALE THREAD COUPLER





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 07:40 PM

SKU
: 4968

MARCA
: DIXON VALVE

MODELO
: 4PM8

Construction:
Zinc Cast sleeve
Machined components are manufactured using solid bar stock.
Nitrile (Buna-N) seals are standard
Stainless steel retaining ring and spring maximize corrosion resistance and extend service life on the 1 piece sleeve. 2-Piece Sleeve has a phosphor bronze spring.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:
Thor Finger-Lock Interchange
Interchanges with National A type, Campbell Double-Lock and Thor PHC series couplings

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1/2"
Burst Pressure	2600 PSI (180 bar)
Factory Part Number	4PM8
Length	3.11" (79.0mm)
Material	Steel
Maximum OD	1.55" (39.4mm)
Maximum Operating Pressure	300 PSI (20 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPTF
Thread Size	1"
Weight Lb	0.8550
Wrench Flat	1-3/8"

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us