DUAL-LOCK P-SERIES THOR INTERCHANGE HOSE BARB COUPLER





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:33 PM

SKU
: 22680

MARCA
: DIXON VALVE

MODELO
: 4PS4

Construction:
Machined components are manufactured using solid bar stock.
Nitrile (Buna-N) seals standard
Stainless steel retaining ring and spring maximize corrosion resistance and extend service life on the 1 piece sleeve. 2-Piece Sleeve has a phosphor bronze spring.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Zinc Cast sleeve

Compatibility & Interchange Data:
Thor Finger-Lock Interchange
Interchanges with National A type, Campbell Double-Lock and Thor PHC series couplings

Safety notes:
Operating pressure for couplings utilizing hose barb connections may be dramatically reduced to that of the hose rating and/or hose end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application. Dixon cannot assume liability for misapplication of production resulting in equipment down-time, lost production, and/or personal injury including death.
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1/2"
Burst Pressure	2600 PSI (180 bar)
Factory Part Number	4PS4
Hose ID	1/2"
Length	3.95" (100.3mm)
Material	Steel
Maximum OD	1.55" (39.4mm)
Maximum Operating Pressure	300 PSI (20 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Weight Lb	0.4900

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us