SHD-SERIES SCHRADER PNEUMATIC MALE THREADED COUPLER





FECHA
: 11/23/2026 10:49 PM

SKU
: 4984

MARCA
: DIXON VALVE

MODELO
: 4SHDM3

Construction:
Machined components are manufactured using solid bar stock.
Stainless steel toggle-pawls and springs. Carbon steel retaining rings.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Adapter components are constructed of brass.
Sleeves are constructed of steel.
Nitrile (Buna-N) seals standard

Compatibility & Interchange Data:
Schrader Twist-Lock Interchange
Parker Twist-Lock, Tomco Series-TL, Foster SHD

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1/2"
Burst Pressure	13400 PSI (924 bar)
Factory Part Number	4SHDM3
Hex	1-1/8"
Length	2.55"
Material	Aluminum
Maximum OD	1.50"
Maximum Operating Pressure	300 PSI (20 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPT
Thread Size	3/8"
Weight Lb	0.4200

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us