20K THREADED COUPLER





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 05:53 PM

SKU
: 4996

MARCA
: DIXON VALVE

MODELO
: 4TDPF4.5-SS

Construction:
Machined components are manufactured using 316 stainless steel bar stock
Stainless steel retaining ring to maximize corrosion resistance and extend service life
Seal Components: Nitrile (Buna-N) seals are standard, providing a temperature range of-40°F to 250°F (-40°C to 121°C)
Couplers have a nitrile anti-extrusion ring, providing resistance to o-ring dynamic impulse pressure damage

Compatibility & Interchange Data:
Jet Stream Screw Type
Spir Star CQD Series, DNP CRS Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	½?
Factory Part Number	4TDPF4.5-SS
Hex	1-1/8? Flat
Length	2.85?
Material	316 Stainless Steel
Maximum OD	1.88?
Maximum Operating Pressure	20,000 PSI
Temperature Range	-40°F to 250°F (-40°C to 121°C)
Thread	9/16" Female MP

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Thread Size	13/16?-16

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us