API LOAD ONLY VALVE







** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 05:50 PM

SKU
: 5269

MARCA
: DIXON VALVE

MODELO
: 5204LSNGP

Applications:
Recommended for crude oil service
Used for bottom loading of petroleum tankers, typically mounted to the piping below each tank compartment using the built in 4" TTMA flange connection.

Specifications:
Manufactured to American Petroleum Institute standard API RP-1004, which allows for positive connection to drop adapters and rack couplers such as the Dixon Bayco 5300/5400 series rack coupler.

Features:
Any required maintenance is simplified, Dixon Bayco API Valves can be completely rebuilt without the need to remove the valve from the tanker
Nose ring is anodized hard coat aluminum, which in most applications will provide years of trouble free service. Nose ring can be rotated to provide a fresh connection service.

Construction:
Aluminum body with anodized hard coat aluminum nose ring and stainless steel hardware
Baylast™ seals
Stainless steel internal springs

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Fuel Compatability	Crude oil, gasoline and diesel, up to E20 and B100 biofuels
Includes	Stainless steel springs and 1/2" FNPT drain port
Length	7"
Material	Aluminum
Factory Part Number	5204LSNGP
Seal	Baylast?
Weight Lb	10.1800

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us