# API LOAD/UNLOAD VALVE






** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 05:50 PM

SKU
: 5272

MARCA
: DIXON VALVE

MODELO
: 5204NGV

Applications:
Used for bottom loading and unloading of petroleum tankers, Load/unload valve permits both terminal loading, and fuel unloading through the valve.

Specifications:
Manufactured to American Petroleum Institute standard API RP-1004, which allows for positive connection to drop adapters and rack couplers such as the Dixon Bayco 5300/5400 series rack coupler.

Features:
Ergonomically curved handle operates on a short 62° degree stroke
Any required maintenance is simplified, Dixon Bayco API Valves can be completely rebuilt without the need to remove the valve from the tanker
Nose ring is anodized hard coat aluminum, which in most applications will provide years of trouble free service. Nose ring can be rotated to provide a fresh connection service.

Construction:
Aluminum body with anodized hard coat aluminum nose ring and stainless steel hardware
Fixed aluminum handle
FKM seals

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Fuel Compatability** | Gasoline and diesel, and up to B100 biodiesel |
| **Length** | 7" |
| **Material** | Aluminum |
| **Factory Part Number** | 5204NGV |
| **Seal** | FKM |
| **Style** | Fixed handle (no sight glass) |
| **Weight Lb** | 11.3650 |



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us