5500-SERIES API COUPLER

FECHA
: 11/23/2026 05:53 PM

SKU
: 27183

MARCA
: DIXON VALVE

MODELO
: 5500H



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

Applications:
Combined with API adapters, these couplers are suitable for rail car and tank truck loading or unloading
Specifications:
Flow rate: 600 GPM at 3 PSI pressure drop; maximum flow rate: 1,000 GPM
Fully compliant with API RP 1004:2003 specifications
Seal operating temperature:
• Baylast:-35°F to 212°F (-37°C to 100°C)
• EPDM:-20°F to 250°F (-28°C to 121°C)
• FKM-B:-10°F to 400°F (-23°C to 204°C)
• FKM-GFLT:-30°F to 400°F (-34°C to 204°C)
• Fluorosilicone:-50°F to 350°F (-45°C to 176°C)
• HiFluor:-15°F to 400°F (-26°C to 204°C)
Features:
Locking five-cam design provides easy alignment and tight connection
Modular design allows various face seal combinations to be compatible with different alternative fuels, performance levels, and applications
Replaceable nose seal can be changed without removing coupler from loading arm
Fully interlocked collar creates a secure connection
4” TTMA inlet mounting flange connection
Ball-end handle for easy and comfortable operation
No special tools needed for maintenance
Construction:
Body: 356 T6 aluminum anodized hard-coat
Cam: stainless steel
Poppet: 356T6 aluminum annodized hard-coat
Seals: FKM-GFLT standard; Baylast, EPDM, Fluoroelastomer, FKM-B, HiFluor®
Link, shaft, pin, crank: hardened 17-4PH stainless steel
Handle: aluminum, stainless steel

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Description	5500 API rack coupler HiFluor with aluminum handle
Factory Part Number	5500H
Weight Lb	21.0000

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us