BALL CONE CHECK VALVE MALE NPT X FEMALE NPT



FECHA
: 11/24/2026 12:46 AM

SKU
: 5667

MARCA
: DIXON VALVE

MODELO
: 61-208

Applications:
For use with water, oil or inert gases. Not recommended for use on or near reciprocating pumps or other similar vibration causing machinery.

Features:
Tight shut-off with liquid media
No radial alignment necessary
Straight through and streamlined for minimum change in velocity
Reinforced PTFE check is spring loaded for fast seating action.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

ESPECIFICACIONES TÉCNICAS

Saturated Steam Pressure	125 PSI
Temperature Range	-20°F to 353°F (-29°C to 178°C)
Thread	male NPT x female NPT
Factory Part Number	61-208
Material	Brass
Pressure Rating	400 PSI WOG, cold non-shock, .5 PSI cracking
Size	2"
Weight Lb	6.2000

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us