BALL CONE CHECK VALVE FEMALE NPT X FEMALE NPT



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 01:03 AM

SKU
: 5682

MARCA
: DIXON VALVE

MODELO
: 62-107

Applications:
For use with water, oil or inert gases. Not recommended for use on or near reciprocating pumps or other similar vibration causing machinery.

Features:
Tight shut-off with liquid media
No radial alignment necessary
Straight through and streamlined for minimum change in velocity
Reinforced PTFE check is spring loaded for fast seating action.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Saturated Steam Pressure	125 PSI
Temperature Range	-20°F to 353°F (-29°C to 178°C)
Thread	female NPT x female NPT
Factory Part Number	62-107
Material	316 Stainless Steel
Pressure Rating	400 PSI WOG, cold non-shock, .5 PSI cracking
Size	1-1/2"
Weight Lb	3.8100

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us