# AIR BRAKE BULKHEAD UNION 62NBH



FECHA
: 11/24/2026 12:53 AM

SKU
: 5783

MARCA
: DIXON VALVE

MODELO
: 62NBH10

Applications:
Designed for use in air brake systems or cab controls

Use:
Utilize ribbed sleeve for compression and positive grip
Compatible tubing: SAE J844 type A and B

Specifications:
Meets D.O.T FMVSS 571.106 and SAE J246

Features:
Positive grip

Construction:
Machined from CA260, CA345 or CA377 brass

Installation
Cut tubing squarely- maximum of 15° angle allowable.
Check that port or mating part is clean and free of debris.
Insert tubing into fittings until it bottoms on seat.
Tighten nut with wrench until one thread remains visible on the fittings body; (this will allow for a number of remakes) or, the nut should be screwed down finger tight, then wrench-tightened according to the tube size used.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Factory Part Number** | 62NBH10 |
| **Flow** | .398" |
| **Hex** | B: 15/16", C: 1" |
| **Length** | 3.04" |
| **Material** | Brass |
| **Temperature Range** | -40°F to 200°F (-40°C to 93°C) |
| **Thread** | Straight |
| **Thread Size** | 13/16"-18 |
| **Tube Size** | 5/8" |
| **Weight Lb** | 0.2000 |
| **Working Pressure** | 150 PSI |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us