DQC E-SERIES STRAIGHT THROUGH INTERCHANGE FEMALE COUPLER WITH LOCKING SLEEVE





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 10:15 PM

SKU
: 6198

MARCA
: DIXON VALVE

MODELO
: 6EF6-S-LS

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings
These couplers have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Machined components are manufactured using 303 stainless steel bar stock
Stainless steel balls, retaining rings and spring maximize corrosion resistance and extend service life.
Nitrile (Buna-N) seals are standard

Available Options:
Contact Dixon® for additional seal material options, pressure ratings and other technical information.

Safety notes:
Do Not Disconnect with pressure in line.
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	3/4"
Burst Pressure	12,000 PSI (827 Bar)
Factory Part Number	6EF6-S-LS
Female Thread	NPTF
Female Thread Size	3/4"-14
Hex	1-1/2"
Length	2.10 (53.3mm)
Material	303 Stainless Steel
Maximum OD	1.64 (41.7mm)
Maximum Operating Pressure	3,000 PSI (207 Bar)
Seal	Buna-N
Temperature Range	-40°F - +250°F (-40°C - +121°C)
Weight Lb	0.6400

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us