AIR BRAKE FEMALE ELBOW



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:31 PM

SKU
: 6281

MARCA
: DIXON VALVE

MODELO
: 70NAB108

Applications:
Designed for use in air brake systems or cab controls

Use:
Utilize ribbed sleeve for compression and positive grip
Compatible tubing: SAE J844 type A and B

Specifications:
Meets D.O.T FMVSS 571.106 and SAE J246
Ref. SAE 100203 BA

Features:
Positive grip

Construction:
Machined from CA260, CA345 or CA377 brass

Installation
Cut tubing squarely- maximum of 15° angle allowable.
Check that port or mating part is clean and free of debris.
Insert tubing into fittings until it bottoms on seat.
Tighten nut with wrench until one thread remains visible on the fittings body; (this will allow for a number of remakes) or, the nut should be screwed down finger tight, then wrench-tightened according to the tube size used.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	70NAB108
Flow	.39"
Material	Brass
Temperature Range	-40°F to 200°F (-40°C to 93°C)
Thread	Straight x Pipe
Thread Size	13/16"-18 x 1/2"
Tube Size	5/8"
Weight Lb	0.2220
Working Pressure	150 PSI

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us