DQC CVV-SERIES EUROPEAN INTERCHANGE FEMALE COUPLER





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 12:08 AM

SKU
: 6556

MARCA
: DIXON VALVE

MODELO
: 8CVVBF8

Construction:
Machined components are manufactured using solid bar stock
Steel retaining rings and springs maximize service life in rugged environments.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Nitrile (Buna-N) seals are standard

Compatibility & Interchange Data:
European Screw-Together Interchange
Inteva STG-Series, Faster CVV-Series, DNP PVV3, Voswinkel Type-HS, Stucchi VD Series

Note:
Threaded sleeves enable easy connection and disconnection while system is under residual pressure only.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	1"
Burst Pressure	17600 PSI (1200 Bar)
Factory Part Number	8CVVBF8
Hex	41mm
Length	3.30" (83.9mm)
Material	Steel
Maximum OD	2.35" (59.8mm)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Maximum Operating Pressure	4400 PSI (300 Bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female BSPP
Thread Size	1"-11
Weight Lb	1.7000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us