
DQC E-SERIES STRAIGHT THROUGH INTERCHANGE FEMALE COUPLER





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:29 PM

SKU
: 6560

MARCA
: DIXON VALVE

MODELO
: 8EBF8-B

Specifications:
Rated pressure for connected Brass Coupler and Brass Plug: 1600 PSI (110 bar) Maximum Working and 6700 PSI (462 bar) burst
Rated pressure for connected Brass Coupler and 303 Stainless Steel Plug: 2000 PSI (138 bar) Maximum Working and 8800 PSI (607 bar) burst

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings
These couplers have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Machined components are manufactured using solid brass
Stainless steel balls, retaining rings and spring maximize corrosion resistance and extend service life.
Nitrile (Buna-N) seals are standard

Available Options:
Contact Dixon® for additional seal material options, pressure ratings and other technical information.

Safety notes:
Do Not Disconnect with pressure in line.
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1"
Burst Pressure	4,800 PSI (331 Bar)
Factory Part Number	8EBF8-B
Female Thread	BSPP
Female Thread Size	1"-11
Hex	1-3/4"
Length	2.41 (61.2mm)
Material	Brass
Maximum OD	2.00 (50.8mm)
Maximum Operating Pressure	1,200 PSI (83 Bar)
Seal	Buna-N
Temperature Range	-40°F - +250°F (-40°C - +121°C)
Weight Lb	0.6800

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us