
DQC TR-SERIES TEMA EUROPEAN INTERCHANGE FEMALE COUPLER





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 12:05 AM

SKU
: 6601

MARCA
: DIXON VALVE

MODELO
: 8TRBF8

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Steel coupler sleeves are hardened to resist deformation and maximize service life.
Nitrile (Buna-N) seals are standard
Couplers have a redundant O-ring sealing system (dual O-rings with inner PTFE back-up ring)
Valve seals are crimped in place to maintain integrity during excessive flow conditions and pressurized connection.

Compatibility & Interchange Data:
TEMA European Interchange
TEMA 3800, 5000, 7500, 10000 Series
CEJN Series 525

Note:
Please contact Dixon for dust caps and dust plugs

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1"
Burst Pressure	12,800 PSI (900 Bar)
Factory Part Number	8TRBF8
Length	3.90" (99.0mm)
Material	Steel
Maximum OD	2.56" (65.0mm)
Maximum Operating Pressure	3,200 PSI (220 Bar)
Seal	Nitrile
Style	Valved
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female BSPP
Thread Size	1"-11
Weight Lb	3.0500

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us