DOUBLE CLAPPER SIAMESE CONNECTION BOTTOM OUTLET



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 06:46 PM

SKU
: 6657

MARCA
: DIXON VALVE

MODELO
: 90DCS4025F-C

Applications:
Provides the required 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply. (250 GPM minimum per inlet.)

Specifications:
UL listed
Factory Mutual approved
ULC Listed

Features:
Exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Branding	Auto-Sprinkler
Factory Part Number	90DCS4025F-C
Finish	Polished Chrome Plated
Inlet	(2) 2-1/2" female NST (NH)
Material	Cast Brass
Maximum Operating Pressure	175 PSI
Outlet	4" female NPT
Weight Lb	17.5600

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us