SINGLE CLAPPER SIAMESE CONNECTION BOTTOM OUTLET



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 10:54 PM

SKU
: 6688

MARCA
: DIXON VALVE

MODELO
: 90SCS4025F

Applications:
Provides the required 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply. (250 GPM minimum per inlet.)

Specifications:
UL listed

Features:
The swing clapper design provides an unobstructed waterway.
Exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes.

Construction:
Single swing clapper with (2) pin lug swivel inlets.

Available Options:
Other thread options are available. Consult Dixon for pricing and availability.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Branding	Auto-Sprinkler
Factory Part Number	90SCS4025F
Inlet	(2) 2-1/2" female NST (NH)
Mandatory Pkg/Box Qty	1
Material	Cast Brass
Maximum Operating Pressure	250 PSI
Origin	U.S.
Outlet	4" female NPT
Weight Lb	12.4000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us