# A-SERIES PNEUMATIC MALE THREADED PLUG

FECHA
: 11/23/2026 08:13 PM

SKU
: 6723

MARCA
: DIXON VALVE

MODELO
: A1M1-B





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

Applications:
A series couplers are intended for use in compressed air service where the convenience of one hand operation and a compact profile is desired.

Specifications:
Rated pressure for connected Brass Coupler & Brass Plug: 500 PSI (35 bar) Maximum Working and 15,500 PSI (1,070 bar) Burst

Construction:
Machined components are manufactured using solid bar stock.

Compatibility & Interchange Data:
Proprietary Astronautics

Safety notes:
Pressure rating given at ambient temperature 70°F (21°C).
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Body Size** | 1/8" |
| **Factory Part Number** | A1M1-B |
| **Flow** | 7 CFM at 100 PSI |
| **Hex** | 7/16" |
| **Length** | 1.30" |
| **Material** | Brass |
| **Maximum OD** | 0.51" |
| **Pressure Rating** | See Product Details |



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Thread** | NPTF |
| **Thread Size** | 1/8" |
| **Weight Lb** | 0.0200 |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us