ADS SPILLGUARD® MONITOR

FECHA
: 11/24/2026 12:24 AM

SKU
: 23001

MARCA
: DIXON VALVE

MODELO
: A210B-24



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

Applications:
Shutdown system for tank cars, tank trucks, barges and ships, suitable for open and closed dome

Specifications:
Cable connectors designed for repeated mating meet IP 65 mechanical and environmental specifications
FM, CSA HAZ Loc Class I Div I, Groups B, C and D
Probe temperature range:-14°F to 212°F (-26°C to 100°C)
Probe pressure rating: 50 PSI with standard fitting, consult Dixon® for applications up to 300 PSI
Sensor suitable for Class I, II, III, Div 1, Groups A, B, C and D when used with supplied controller and cable lengths of 10,000' or less
Output relay contacts 2 form C (2PDT) rated 2 amps at 120/240 VAC, 1 form C (SPDT) with optional latching circuit and reset switch

Features:
Rugged, explosion proof, weather, chemical and corrosion resistant
LED status lights visible through glass cover
Inserts into tank through standard 1/2" NPT fitting
Probe can be portable or permanently installed in the vessel
Laser engraved graduated rod with 1/4 graduations
Probe-to-controller cable protected by stainless steel interlocking armor sheath and heavy duty latching connectors at both ends
Fail safe design, unit trips in the event of an open or shorted cable or loss of power
Choice of capacitance, conductivity, ultrasonic, temperature or float sensors
Input power:120 VAC, 240 VAC or 24 VDC, 2.5 watts
Output relay de-energizes on high level, broken or shorted sensor cables or loss of power
Sensor excitation open circuit voltage 8 VDC, short circuit current 8MA with

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

built-in FM approved barrier
Optional self test feature, tilt and ground verification interlocks and latching circuit available

Construction:
Wetted materials: 316 stainless steel and PTFE standard, other materials available
Controller housing NEMA 4X, NEMA 7, Explosion Proof, Class I, II, Groups B, C and D

Available Options:
Standard cable lengths: 15', 25' and 50', other lengths available
Insertion lengths 4" to 60" standard, other lengths available

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Description	with bypass timer, 24 VDC
Factory Part Number	A210B-24
Pressure Rating	50 PSI with standard fitting, consult Dixon® for applications up to 300 PSI
Temperature Range	-14°F to 212°F (-26°C to 100°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us