AIR RELIEF VALVE FIXED PRESSURE FEMALE NPT



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:24 PM

SKU
: 25889

MARCA
: DIXON VALVE

MODELO
: A2180/6

Applications:
Designed specifically for use on trailer tanks containing dry bulk products. If a system blockage were to occur the valves are designed to vent to atmosphere once the valve pressure setting is achieved.

Use:
Trailer/Tank Mounted Air Relief Valve

Specifications:
Relieving capacity: 500 to 950 SCFM

Features:
Installed cup seal deters tampering
Bayloy body eliminates thread galling

Construction:
Bayloy vent cowl with aluminum upper
Bronze poppet
White Food Grade Silicone Diaphragm

Available Options:
PVC coated wire lanyard available for securing air relief valves

Note:
Relieving capacity (SCFM) varies dependent upon model and pressure setting. For specific rates please contact Dixon.

Safety notes:
Not intended for blower service (for blower service applications see the 2182 series air relief valves)
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Component Material	White Food Grade Silicone Diaphragm
Factory Part Number	A2180/6
Female Thread	NPT
Female Thread Size	2"
Material	Aluminum
Pressure Setting	6 PSI
Set Pressure Tolerance	+1/0 PSI
Weight Lb	4.5000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us