A-SERIES PNEUMATIC REUSABLE BARB PLUG





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 06:03 PM

SKU
: 23005

MARCA
: DIXON VALVE

MODELO
: A2E2

Applications:
A series couplers are intended for use in compressed air service where the convenience of one hand operation and a compact profile is desired.

Specifications:
Rated pressure for connected Brass Coupler & Steel Plug: 1,000 PSI (70 bar) Maximum Working and 8,000 PSI (550 bar) Burst

Construction:
Machined components are manufactured using solid bar stock.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:
Proprietary Astronautics

Safety notes:
Pressure rating given at ambient temperature 70°F (21°C).
Operating pressure for couplings utilizing hose barb connections may be dramatically reduced to that of the hose rating and/or hose end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application.

Dixon cannot assume liability for misapplication of production resulting in equipment down-time, lost production, and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1/4"
Factory Part Number	A2E2
Hex	9/16"
Hose ID	1/4"
Hose OD	1/2"
Length	1.97"
Material	Steel
Maximum OD	0.68"
Pressure Rating	See Product Details
Weight Lb	0.0705

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us