TRUESEAL? CHECK VALVE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:54 PM

SKU
: 6798

MARCA
: DIXON VALVE

MODELO
: A4VC4-MG

Applications:
Push-to connect check valves ensure protection against reversal of flow. The valves have an arrow molded into the body to indicate the direction of flow. Valves are designed for connection with either thermoplastic or soft metal tubing and are intended for use with liquids only.

Specifications:
NSF-51 listed

Construction:
Body Material: Acetal
O-ring: EPDM
Metal Grip Edge: 300 stainless steel

Safety notes:
Intended for use with liquids only
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Cracking Presure	1/3 PSI
Factory Part Number	A4VC4-MG
Material	Acetal
Maximum Operating Pressure	150 PSI (dependent on tubing used)
Seal	EPDM
Temperature Range	34°F to 150°F (1°C to 65°C)
Tube OD	1/4"
Weight Lb	0.0200

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us