AIR KING® 2-LUG FEMALE NPT END



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 10:29 PM

SKU
: 6843

MARCA
: DIXON VALVE

MODELO
: AB13

Use:
Use of supplied safety clip guarantees the fittings are properly connected because the safety pin will not go through the holes in mating fittings until couplings are locked in place. Only one Air King safety clip or wire type retainer is required for each Air King universal coupling.
Air King is for air and water service only

Specifications:
Air King meets pressure requirements as specified in A-A-59553 commercial item description superseding Mil Spec.WWC-633D.

Features:
Safety clip included
Supplied with rubber washer, part # AWR4

Safety notes:
Air King is for air and water service only
Never use any Air King coupling for steam service!
The use of an Air King safety clip or wire type retainer is necessary to ensure Air King universal couplings will not become accidentally disconnected.
To provide protection against coupling breakage and related hazards, Dixon recommends the use of a whip hose.
Pressure rating given at ambient temperature 70°F/21°C
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	AB13
Material	Brass, global investment cast
Pressure Rating	150 PSI (1 MPa)
Seal	Rubber
Size	1"
Weight Lb	0.4900

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us