AG-SERIES AGRICULTURAL POPPET VALVE FEMALE THREADED PLUG





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 01:13 AM

SKU
: 6969

MARCA
: DIXON VALVE

MODELO
: AG8F8-PV

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Steel nipples are hardened to provide heavy duty performance and resist brinelling.

Compatibility & Interchange Data:
Pioneer Agricultural Interchange
Parker/Pioneer 4000 Series, Faster NS/NV Series
Safeway Series-S20, Stucchi IR-Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	1"
Burst Pressure	13000 PSI (900 Bar)
Factory Part Number	AG8F8-PV
Hex	1-5/8"
Length	2.71" (68.8mm)
Material	Steel
Maximum OD	1.76" (44.7mm)
Maximum Operating Pressure	3000 PSI (200 Bar)
Thread	Female NPTF

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Thread Size	1" - 11-1/2
Weight Lb	0.6000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us