
ANSI SPLIT FLANGE- SERIES SF



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 06:59 PM

SKU
: 23074

MARCA
: DIXON VALVE

MODELO
: ANSI25

Applications:
Provides a direct connection between a grooved adapter and an ANSI Class 125 and 150 raised face flanged component.

Use:
Can be used with flat face flanges by removing the raised projections on the outside face of the flange

Specifications:
Underwriters Listed
Factory Mutual approved
Bolts: 4
Bolt Size: 5/8"
Bolt Length: 5/8"

Features:
Comparable to Victaulic's #741 and Grinnell's #7012

Construction:
Rust inhibiting paint
EPDM gasket

Available Options:
Buna gaskets are available upon request, contact Dixon.

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	ANSI25
Material	Ductile Iron
Maximum Operating Pressure	300 PSI at 70°F(21°C)
Nominal Size	2-1/2"
Pipe OD	2.875"
Weight Lb	4.5200

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us