GLOBAL ADJUSTABLE PRESSURE RESTRICTING ANGLE VALVE MALE OUTLET



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:53 PM

SKU
: 7200

MARCA
: DIXON VALVE

MODELO
: AVAPR150F-I

Applications:
Pressure restricting valves are used when flowing water pressure needs to be controlled.
NFPA requires restricting valves where the inlet pressure exceeds 100 PSI. Unlike the pressure regulating type of valve, the restricting valve has no effect on the static pressure of a system.

Available Options:
Consult Dixon for pricing and availability of other thread options.

How it works:
Restricting valves are angle valves with preset orifices which restrict the volume of water and thereby lower the pressure of the flowing water.

Note:
The restricting device can be manually bypassed if required by opening the valve fully. Simply pull the pin to allow the yoke to fall back from the valve stem to allow the valve to be opened fully. When the valve needs to be restricted again, slide the yoke back into place to be NFPA compliant.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Inlet	1-1/2" female NPT
Material	Brass
Outlet	1-1/2" male NST (NH)
Factory Part Number	AVAPR150F-I
Weight Lb	5.0000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us