THERMAL-GARD? ELEVATED TEMPERATURE SPRAY NOZZLE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 08:32 PM

SKU
: 7223

MARCA
: DIXON VALVE

MODELO
: AWSG-TG

Features:
Nozzle protects the operator from extreme hot water temperatures that exceed the comfort zone of standard hot water nozzles.
Thermal insulating sleeve reduces overall heat during elevated temperature conditions.

Construction:
Lightweight aluminum alloy body reduces overall weight.
Aluminum alloy body is electroless nickel plated for additional corrosion protection.
Stainless steel lever handle is coated for additional thermal protection, and operator comfort.
Black cover
3/8" female NPT inlet
Required special rigid, stainless steel adapter, (3/8" male NPT x 1/2" female NPT) included

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	AWSG-TG
Flow	12.5 GPM
Material	Aluminum
Temperature Range	140°F to 200°F (60°C to 93°C) Water
Weight Lb	2.1700
Working Pressure	150 PSI

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us