Y-BALL CHECK VALVE

FECHA
: 11/23/2026 08:26 PM



SKU
: 8132

MARCA
: DIXON VALVE

MODELO
: B45BY-R300

** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

Specifications:
3A authorized 58-00
Clamp & Cap Size: 4"
Ball diameter: 3.6

Features:
Field serviceable (no special tools required)
Replace seat instead of entire valve

Construction:
Two-piece construction
PTFE ball
All metal product surfaces are 316L stainless steel construction

How it works:
When liquid flows through the valve, the ball is forced into the branch of the valve allowing full fluid flow. When the liquid stops, equalizing the pressure, the ball drops back into the seat, preventing backflow. Should reverse flow occur, the differential pressure will caused the ball to seal firmly against the seat preventing leakage.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	B45BY-R300
Material	316L Stainless Steel
Maximum Operating Pressure	150 PSI
Seat	EPDM/CF8M stainless
Size	3"
Temperature Range	15°F to 200°F (-9.4°C to 93°C)
Weight Lb	10.8700

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us