AIR BLOW CHECK VALVE HOSE BARB



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 10:52 PM

SKU
: 8152

MARCA
: DIXON VALVE

MODELO
: B45CC-R300

Applications:
The air blow check valve is designed to pressurize lines with air to clean out product or cleaning solutions. It is fail-safe because the simple air-to-open, spring-to-close mechanism prevents backflow. Can be used with a check valve.

Specifications:
3A authorized 58-00

Construction:
EPDM stem seat and gasket

Note:
Filter disc (optional) must be used when installed for Accepted Practice 3A 604-05, Supplying Air under Pressure in Contact with Milk, Milk products and Product Contact.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	B45CC-R300
Material	316L Stainless Steel
Maximum Operating Pressure	145 PSI
Maximum Temperature	212°F (100°C)
Seat	EPDM stem seat and gasket
Size	3"

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us