B5102 SERIES BUTTERFLY VALVE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:47 PM

SKU
: 8391

MARCA
: DIXON VALVE

MODELO
: B5102V400-A

Specifications:
Break torque: 495 in. lbs.
Assembly torque: 43.2 in. lbs.
Flow coefficient: 800 CV

Features:
All sizes use only 3/4" of line space
The grooved clamp housing connects directly to the corresponding sanitary clamp size
100% tested / 100% inspected
Field serviceable (no special tools required)

Construction:
All wetted surfaces are sanitary finish 316L stainless steel
PTFE valve disc bushings reduce friction and increase cycle life
3-position reversible handle

Available Options:
Various automatic operations available
Can be modified for lockout / tagout

Note:
Pressure rating (PSI), Flow Coefficient (CV), Assembly Torque (in. lbs.) and Break Torque (in. lbs.) information supplied is based on water media at 68°F

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	B5102V400-A
Material	316L Stainless Steel
Pressure Rating	70 PSI, 0.4 inches Hg vacuum @ 68°F minimal line
Seat	FKM
Size	4"
Temperature Range	15°F to 200°F (-9.4°C to 93°C)
Weight Lb	4.7950

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us