BR-SERIES PNEUMATIC HOSE BARB PLUG





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:11 PM

SKU
: 23345

MARCA
: DIXON VALVE

MODELO
: BR1S1.25-B-E-7

Construction:
Machined components are manufactured using solid brass bar stock.
Machined components are plated with chrome-over-nickel plating.

Compatibility & Interchange Data:
Rectus 21KA, Tomco Series SC, CEJN Series 223

Safety notes:
Operating pressure for couplings utilizing hose barb connections may be dramatically reduced to that of the hose rating and/or hose end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application. Dixon cannot assume liability for misapplication of production resulting in equipment down-time, lost production, and/or personal injury including death.
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1/8"
Burst Pressure	7000 PSI
Factory Part Number	BR1S1.25-B-E-7
Hex	9/16"
Hose ID	4mm
Length	1.26"
Material	Brass
Maximum OD	0.35"
Maximum Operating Pressure	300 PSI
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Weight Lb	0.0300

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us