# BAYONET STYLE DRY DISCONNECT 90° SWIVEL COUPLER X FEMALE NPT




** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 02:20 AM

SKU
: 9256

MARCA
: DIXON VALVE

MODELO
: BS62-200

Applications:
Bayonet dry disconnect fittings are ideally suited for the spill-less transfer of petroleum products such as fuel oil, lube oil blending, and tank truck delivery. The design of the Bayco bayonet dry disconnect system ensures a spill free connection, fluid cannot flow until couplings are connected together and the valve is opened. The coupling can then not be disconnected until the valve handle is closed.

Specifications:
Canadian registration number CRN# OH14055 all provinces

Features:
Helps eliminate the possibility of costly spills

Construction:
Swivels have a standard ZERK fitting

Compatibility & Interchange Data:
Interchangeable with the Emco Wheaton™ Dry Break™

Note:
Rubber dust plugs with stainless steel chains are available to protect the coupler from contamination and damage.

Safety notes:
For pressure ratings at other temperatures contact Dixon®.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Factory Part Number** | BS62-200 |
| **Material** | Anodized Hard Coat Aluminum |
| **Maximum Operating Pressure** | 85 PSI at 70°F (21°C) |
| **Seal** | FKM |
| **Size** | 2" |
| **Weight Lb** | 3.8000 |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us