BAYONET STYLE DRY DISCONNECT STRAIGHT SWIVEL COUPLER X FEMALE NPT



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 01:36 AM

SKU
: 9310

MARCA
: DIXON VALVE

MODELO
: BSS61-200

Applications:
Bayonet dry disconnect fittings are ideally suited for the spill-less transfer of petroleum products such as fuel oil, lube oil blending, and tank truck delivery. The design of the Bayco bayonet dry disconnect system ensures a spill free connection, fluid cannot flow until couplings are connected together and the valve is opened. The coupling can then not be disconnected until the valve handle is closed.

Specifications:
Canadian registration number CRN# OH14055 all provinces

Features:
Helps eliminate the possibility of costly spills

Construction:
Swivels have a standard ZERK fitting

Compatibility & Interchange Data:
Interchangeable with the Emco Wheaton™ Dry Break™

Note:
Rubber dust plugs with stainless steel chains are available to protect the coupler from contamination and damage.

Safety notes:
For pressure ratings at other temperatures contact Dixon®.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	BSS61-200
Material	Anodized Hard Coat Aluminum
Maximum Operating Pressure	85 PSI at 70°F (21°C)
Seal	Buna
Size	2"
Weight Lb	3.4000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us