3-WAY MULTI-PORT SANITARY STAINLESS STEEL BALL VALVE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 01:03 AM

SKU
: 9733

MARCA
: DIXON VALVE

MODELO
: BV3SCLF075C-A

Specifications:
Break torque: 91 in. lbs.

Features:
Full port design
Blow-out proof stem
Live-loaded stem packing
Lock-out, tag out

Construction:
CF8M stainless body, ends and ball
25% carbon reinforced tetrafluoroethylene seat is specified for higher temperature pressure applications. Ideal for steam and thermal fluid applications. Higher cycle life than RTFE.
ISO 5211 mounting pad

Available Options:
Private label handle covers available

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	BV3SCLF075C-A
Material	Stainless Steel
Port	L Port
Pressure Rating	1000 PSI WOG
Seat	25% carbon reinforced PTFE
Size	3/4"

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us