3-WAY MULTI-PORT SANITARY STAINLESS STEEL BALL VALVE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:33 PM

SKU
: 9765

MARCA
: DIXON VALVE

MODELO
: BV3SSLF150C-A

Specifications:
Break torque: 474 in. lbs.

Features:
Full port design
Blow-out proof stem
Live-loaded stem packing
Lock-out, tag out

Construction:
CF8M stainless body, ends and ball
50% stainless steel reinforced PTFE seat is specified for higher temperature pressure applications in a sanitary process. Food grade material.
ISO 5211 mounting pad

Available Options:
Private label handle covers available

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	BV3SSLF150C-A
Material	Stainless Steel
Port	L Port
Pressure Rating	400 PSI WOG
Seat	50% stainless steel reinforced PTFE
Size	1-1/2"

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us