WILKERSON FRL'S C16 COMPACT COMBINATION UNIT



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 07:21 PM

SKU
: 26135

MARCA
: DIXON VALVE

MODELO
: C16-02MMB

Features:
Manual Drain
Metal Bowl with Sight Glass
F16 series Filter has a 5 micron element and 5 oz. bowl
R16 series Regulator is self relieving, has a 0-125 PSI adjusting range and is supplied with a GC230 gauge
L16 series Lubricator has a 5 oz. bowl, an adjustable oil feed and a full view sight dome
(2) modular sleeves, (2) mounting brackets (sleeve and bracket) and (2) end blocks are included

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 150 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Description	Manual Drain, Metal Bowl with Sight Glass
Factory Part Number	C16-02MMB
Flow	36.1 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	200 PSIG (13.8 Bar)
Port	1/4"
Temperature Range	32°F to 175°F (0°C to 79°C)
Weight Lb	5.9100

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us