GROOVED STANDARD COUPLING- SERIES S, STYLE 11



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:38 PM

SKU
: 23381

MARCA
: DIXON VALVE

MODELO
: C24BU

Applications:
Designed for a wide range of applications including commercial/industrial construction, mining, and process piping.

Specifications:
Underwriters Listed
Factory Mutual approved
Bolts: 2
Bolt Size: 7/8"
Bolt Length: 5"

Features:
Housing design allows for optimum strength without excessive casting weight
Comparable to Victaulic's #77 and Grinnell's #7001

Construction:
Rust inhibiting paint

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	C24BU
Material	Ductile Iron
Max. End Load Lbs.	102141
Maximum Operating Pressure	800 PSI at 70°F (21°C)
Nominal Size	12"
Pipe OD	12.75"
Seal	Buna-N
Weight Lb	29.2900

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us