WILKERSON FRL'S C26 STANDARD COMBINATION UNIT



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:29 PM

SKU
: 26161

MARCA
: DIXON VALVE

MODELO
: C26-04M

Features:
Manual Drain
Transparent Bowl and Guard
F26 Series Filter has a 5 micron element and a 10 oz. bowl
F26 series Regulator is self-relieving with a 0-125 PSI adjusting range and is supplied with a GC230 gauge
L26 series Lubricator has a 10 oz. bowl, an adjustable oil feed and a full view sight dome
(2) modular sleeves, (2) mounting brackets (sleeve and bracket) and (2) end blocks are included

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 150 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Description	Manual Drain, Transparent Bowl and Guard
Factory Part Number	C26-04M
Flow	128 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	1/2"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	8.5400

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us