WILKERSON FRL'S C28 STANDARD COMBINATION UNIT



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:47 PM

SKU
: 26173

MARCA
: DIXON VALVE

MODELO
: C28-06M

Features:
Manual Drain
Transparent Bowl and Guard
Quick disconnect bowl / bowl guard
Modern design and appearance
F28 series Filter has a 5 micron element and a 6 oz. bowl
R28 series Regulator is self-relieving with a 0-125 PSI adjusting range and is supplied with a GC230 gauge
L26 series Lubricator has a 6.11 oz. bowl, an adjustable oil feed and a full view sight dome
(2) end blocks and (2) mounting brackets with joiner set and port O-ring are included

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 150 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Description	Manual Drain, Transparent Bowl and Guard
Factory Part Number	C28-06M
Flow	110 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	3/4"
Temperature Range	32°F to 150°F (0°C to 65.5°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Weight Lb	6.4100

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us