WILKERSON FRL'S C31 COMBINATION UNIT WITH PROTECTIVE FRAME



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 05:39 PM

SKU
: 26181

MARCA
: DIXON VALVE

MODELO
: C31-08FRAME

Applications:
Provides downstream air preparation with protection and convenience.

Features:
Heavy duty frame protects air prep components
C31-08AMB 1" FRL with metal bowls and auto drain filter
BBLV100 1" brass ball valve and AM12 air king on inlet port
BBV100DTW 3-way ball valve installed between regulator and lubricator provides option for non-lubricated air

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 150 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	C31-08FRAME
Flow	320 SCFM
Maximum Operating Pressure	250 PSIG
Port	1"
Temperature Range	40°F to 150°F (4.4°C to 65.6°C)
Weight Lb	75.0000

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us