HYDRAULIC 4-BOLT FLANGE SAE PORT



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 10:36 PM

SKU
: 9848

MARCA
: DIXON VALVE

MODELO
: C611062020SAE

Applications:
Flange adapters for hydraulic systems make installation of components easier, especially in applications with limited space.

Specifications:
SAE J518-1 / ISO 6162-1

Features:
Standard pressure
Flanges are constructed with an O-ring seal to eliminate leakage
Flat face flange must be used with O-ring flange
No bolt kit is included with flat face flange

Construction:
Pad size: 1-1/4"

Available Options:
Also available in 316L stainless steel, contact Dixon

Note:
Connection type opposite 4-bolt flange connection can de-rate maximum working pressure

Safety notes:
Pressure rating given at ambient temperature 70°F
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	C611062020SAE
Fitting Type	Flat Face
Material	Carbon Steel
Maximum Operating Pressure	4000 PSI (28 MPa)
Port	1-1/4"
Style	Code 61
Thread Size	1-5/8"-12
Torque	Grade 8 UNC: 68 lb-ft
Weight Lb	1.6100

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us